

(65)

BE - Sem VII - CBSSG - Civil Engineering

LSM RCS

23/11/15

QP Code : 5851

(3 HRS)

Maximum Marks: 80

N.B.

- 1. Question no. 1 is compulsory. Attempt any THREE out of remaining FIVE questions.
- 2. Assume suitable data if necessary but justify the same.
- 3. Use of IS code is NOT permitted.

Q.1 Attempt any FOUR. 20

- a. What is Bond? How can we increase the bond between steel and concrete? (5)
- b. State the assumptions made in the Limit State of Collapse (flexure) in RCC. Also draw strain and stress diagram across the section. (5)
- c. What are the functions of distribution steel in one way slab? (5)
- d. What are the steps for the design of a column subjected to axial load and biaxial bending? (5)
- e. Write any four assumptions in Ultimate Load Design method in RCC. Also sketch the stress block used in this method. (5)
- f. What is combined footing? Sketch plan and elevation of any two types of combined footing. (5)

Q.2 Attempt the following. 20

- a. Determine the limiting moment of resistance of the beam having dimensions 300mmX 550 mm (effective), is reinforced with 4-20mm dia. bars in tension zone. Use (i) M₂₀ concrete and Fe₄₁₅ steel. (ii) M₂₀ concrete and Fe₂₅₀ steel. (10)
- b. A beam of size 300 x 550 mm overall, is subjected to a factored bending moment of 260 kNm. Compute the reinforcement required at an effective cover of 50 mm to compression and tension reinforcement. Use M 20 concrete and Fe 415 steel. (10)

d'/d	0.05	0.100	0.15	0.20
f _{sc} (MPa)	355	353	342	329

Q.3 Attempt the following. 20

- a. A reinforced concrete beam of 300 x 550 mm overall is reinforced with 6 bars of 20 mm φ HYSD steel of grade Fe 415, placed at an effective cover of 50 mm. The beam carries a factored UDL of 120 kN/m over a simply supported clear span of 5 m. Design the shear reinforcement if two bars are bent up at support making an angle of 45°. Use M 20 and Fe 415. Also sketch the shear reinforcement details. (10)

MUPD15025 ANJUMAN-ISLAMIS KAISER ENGINEERING, NEW PANVEL 23-11-2015 09:44:14

pt%	0.50	0.75	1.0	1.25	1.5	1.75
τ_c MPa	0.48	0.56	0.62	0.67	0.72	0.75

- b. A tee beam having 1250 mm effective width of flange has a thickness of flange equal to 115 mm. The effective depth of the beam is 550 mm and width of the web is 300 mm. It is reinforced with 8 bars of 20 mm ϕ on the tension side. Determine limiting moment of resistance if M 20 concrete and Fe 415 steel is used. (10)

Q.4 Attempt the following. 20

- a. A short RCC column is subjected to a factored load of 1900 kN within the limit of minimum eccentricity. Design the column and show reinforcement details. Use M 30 and Fe 415. (6)
- b. A hall of a residential building measures 4.2 m x 6m. It is supported by 230 mm thick wall on all four sides. Design the simply supported slab using M 20 and HYSD Fe 415 steel. Assume the live load on the slab as 3kN/m^2 and the floor finish load as 1kN/m^2 . Apply checks for shear, deflection and development length. Sketch the reinforcement details along both spans. (14)

L_y/L_x	1.3	1.4	1.5	1.75
α_x	0.093	0.099	0.104	0.113
α_y	0.055	0.051	0.046	0.037

Q.5 Attempt the following. 20

- a. Write step by step procedure to design isolated footing of uniform thickness. (4)
- b. A rectangular beam of size 250 x 400 mm overall is reinforced with 3 bars of 16 mm ϕ as tension reinforcement. It is subjected to a shear force of 18 kN and a bending moment of 18 kN m. In addition to this it also carries a torsional moment of 1.8 kN m. Design the beam for combined BM, SF and TM. (8)
- c. A simply supported one way slab over a passage of a public building has a clear span of 2.5 m. It is supported on 230 mm thick wall. Design the slab using M 20 and Fe 415 steel. Assume live load as 5kN/m^2 and floor finish load as 0.75kN/m^2 . Apply all required checks. Sketch the reinforcement details. (8)

- Q.6 Design the combined footing for two columns C1 and C2 of size 500 x 500 mm each, spaced at 4 m apart, carrying an axial compressive load of 1500 kN on each column. The available width restriction is 2.2m. The SBC of the soil is 150kN/m^2 . Use M 25 and Fe 415. Sketch reinforcement details. 20