FW-Con.10934-16.

QP Code: 31122

WEN PANEL 2305 20 10 23:55:06 [Total Marks: 80 (3 Hours) 1) Question number one is compulsory NB: 2) Attempt any three questions from remaining questions 3) Assume suitable data wherever necessary and state it clearly 4) Figures to the right indicates maximum marks 01 Attempt any five of the following a) Differentiate between 4- Stroke and 2-Stroke Engine What are the requirements for spark plug What is Dissociation? What are its effects? c) d) Explain stages of combustion in CI engines. Explain any one type of cooling system in engine with its advantages. e) What are the limitations of simple carburetor? 1) What are the functions of lubrication? State required properties of lubricating Q2 a) In a Trial of single cylinder diesel engine the following observations were b) made: Calorific value of fuel = 43890 kJ/kg, Oil constimption = 10.2 kg/h, Speed = 1900 rpm, Air consumption =3.8 kg/min, compression ratio =15, Torque = 186 Nm. Quantity of cooling water resed = 15.5 kg/min, Temp. rise-36°C, Exhaust gas temp. 410°C, Room Temp. = 20°C, Cp of exhaust gases = 1.17 KJ/kg kCalculate: i) B.P ii) BSFC iii) Heat Balance sheet on minute basis. Q3 a) Explain with sketch working of battery ignition system with its advantages and dis-advantages. b) A perfect gas at 1 bar and 290 Kundergoes ideal diesel cycle. The maximum pressure of the cycle is 50 bar. The volume at the beginning of compression is 1m3 and after constant pressure heating is 0.1m3. Determine the temperature at all salient points of the cycle and also find out the efficiency of the cycle. Take v = A for the gas. Q4 a) What is super charging and turbo charging? Describe in brief the methods of (10) turbo charging2 (10)The dimensions of carburetor are as follows. Venturi the at diameter is 20 mm with coefficient of discharge of 0.85, Fuel orifice trameter is 1.25 mm with coefficient of fuel flow of 0.66, the fuel surface is 5 mm below the throat. Compute air fuel ratio for depression of 0.07 bar when nozzle lip is neglected 2) Air-fuel ratio when nozzle lip is considered TURN OVER