Q.P.Code 31328

	(3 Hours) [Total Marks: 80)
N.B. :	 Question No.1 is compulsory. Attempt any three questions out of remaining five questions. Assume suitable data if necessary and justify the same. 	2009.
Q1	 Question No.1 is compulsory. Attempt any three questions out of remaining five questions. Assume suitable data if necessary and justify the same. Answer the following questions. Explain the classification of magnetic material. Explain the different insulating materials used in transformer. Discuss the factors affecting the size of motor. Explain the advantages of Energy Efficient Motor. A) Derive the output equation for a three induction motor.	20
Q2	A) Derive the output equation for a three induction motor. B) In the design of a 3 phase, 440 V, 50 Hz, 3.75 KW, delta connected induction motor, assume the specific electric loading of 23000ac/m, specific magnetic loading of 0.45 wb/m². Full load efficiency 85%, power factor 0.84, stator winding factor 0.95 and estimate the following: 1) Stator core dimension 2) Number of stator slots and winding turns, 3) conductors per slot	10
Q3	 A) Derive the output equation for a three core type transformer. B) Calculate the per unit leakage reactance of a 3 phase,50 Hz, 11000/440V, 315 KVA, delta/star core type transformer with data LV Winding: Inner diameter = 0.22mm, Outer diameter = 0.26mm, Area of conductor = 170mm², Length of coil = 0.5 meter, Voltage per turn = 8V, HV Winding: Inner diameter = 0.29mm, Outer diameter = 0.36mm, Area of conductor = 5.4mm² Resistivity = 0.021 Ω/m/mm² 	10 10
Q4	A) Describe different types of cooling methods for transformer.B) Explain various types of winding used in case of transformer.	10 10
Q5	A) Discuss the various types of leakage fluxes in induction motor with neat diagram. Discuss the various factors affecting the selection of number of stator slots and rotor slots in case of three phase induction motor.	10

QP Code: 31328

20 sassisted of the content of the c