**QP Code: 31146** 

**Duration: 3 Hrs** 

Max.Marks

An echanism of antenna with single wire system.

An the use of Richard transformation and Kurodas Identity in RF filter design

Derive an expression for array of two isotropic sources with same amplitude and in phase.

Explain the RF behavior of resistor, capacitor and inductions is the design procedure for filter ethod. (1) Question No. 1 is Compulsory (2) Solve any three from remaining questions (3) Assume suitable data wherever required. QuestionNo. 01 (a) (b) (c) (d) Q2 (a) (b) Q3 (a) Design a maximally flat LPF with a cut off-frequency of 2 GHz. The generator and load impedance is 50  $\Omega$  with 15 dB insertion loss at 3GHz with discrete LC components. (b) 10 Derive an expression for array factor of N element linear array, where all elements are equally fed and spaced. Also find the expression for the position of principle maxima, nulls and secondary maxima. A radio link has 15 watt transmitter connected to an antenna of 2.5 10 Q4 (a)  $m^2$  effective aperture at 5 GHz. The receiving antenna has an effective aperture of  $0.5 m^2$  and is located at a 15 km line of sight distance from transmitting antenna. Assume lossless antennas. Find power delivered to the receiver. (b) 10 Derive an expression for E field and H field of infinitesimal dipole

[TURN OVER

FW-Con.10940-16.

Max. Marks: 80 Marks

2 FW-Con.10 What is the folded dipole Antenna? Draw its typical structure and Q5 (a) 10 explain working mechanism. Give its advantages.