



Knowledge Resource & Relay Centre (KRRC)

AIKTC/KRRC/SoET/ACKN/QUES/2021-22/

Date: 02/08/2022School: SoET-REV. C-SCHEME Branch: CIVIL ENGG. SEM: VI

To,
Exam Controller,
AIKTC, New Panvel.

Dear Sir/Madam,

Received with thanks the following **Semester/Unit Test-I/Unit Test-II (Reg./ATKT)** question papers from your exam cell:

| Sr. No. | Subject Name | Subject Code | Format | | No. of Copies |
|---------|---------------------------------------|--------------|--------|----|---------------|
| | | | SC | HC | |
| 1 | Design and Drawing of Steel Structure | CE-C601 | | ✓ | |
| 2 | Water Resources Engineering | CE-C602 | | ✓ | |
| 3 | Geotechnical Engineering-II | CE-C603 | | ✓ | |
| 4 | Environmental Engineering | CE-C604 | | ✓ | |
| 5 | Department Optional Course-2 | CE-C605 | | ✓ | |
| | Construction equipment & Techniques | | | ✓ | |
| | Traffic engineering & management | | | ✓ | |
| | | | | | |
| | | | | | |

Note: SC – Softcopy, HC - Hardcopy

(Shaheen Ansari)
Librarian, AIKTC

CE

Curriculum Scheme: Rev2019 _ 'C'-Scheme

Examination: Third year Civil Semester - VI

Course Code: CE-C601

Course Name: Design and Drawing of Steel Structures

Time: 2 hour 30 minutes

Max. Marks: 80

| | |
|------------|---|
| | <p>NB</p> <ol style="list-style-type: none"> 1. Attempt all four questions each carrying weightage of 20 marks. 2. Use of IS 800 & steel table is permitted during the exam. 3. Draw neat sketches wherever necessary. 4. Assume suitable data if needed & justify the same. |
| Q1. | Choose the correct option for the following questions. All the questions are compulsory and carry equal marks |
| 1) | An ISMC 300 @ 0.363 KN/m is connected to a 12mm thick gusset plate. The size of the weld is 6 mm. Assume site welding. The strength of the weld is nearly..... |
| Option A: | 600 N/mm |
| Option B: | 750 N/mm |
| Option C: | 663 N/mm |
| Option D: | 450 N/mm |
| 2) | Calculate the net area of an angle ISA 90×90×8 which is connected to the gusset plate through a single leg. Bolts used are M20 grade 4.6. (Assume standard clearance) |
| Option A: | 1200 mm ² |
| Option B: | 1100 mm ² |
| Option C: | 1000 mm ² |
| Option D: | 1500 mm ² |
| 3) | The shear lag width for ISA 75×75×10 connected by the bolt is..... (Assume gauge distance = 40 mm) |
| Option A: | 100 mm |
| Option B: | 105 mm |
| Option C: | 150 mm |
| Option D: | 120 mm |
| 4) | An ISA 150×75×10 is connected to a gusset plate of thickness 12mm by four M18 bolts of grade 4.6. The tensile strength governed by yielding of gross section of the angle if gusset is connected to the longer leg is..... |
| Option A: | 450 kN |
| Option B: | 250 kN |
| Option C: | 390 kN |
| Option D: | 490 kN |
| 5) | An ISMB 300 is to be used as a compression member. Considering the buckling about y-y axis, the corresponding buckling class as per IS 800: 2007 will be..... |
| Option A: | a |
| Option B: | b |
| Option C: | c |
| Option D: | d |

| | |
|-----------|--|
| 6) | A column section with buckling class 'c' has a minimum radius of gyration of 32 mm. The effective length of the column is 3200 mm. The design compressive stress for $f_y = 250$ MPa (as per IS 800: 2007) will be..... |
| Option A: | 102 N/mm ² |
| Option B: | 104 N/mm ² |
| Option C: | 105 N/mm ² |
| Option D: | 107 N/mm ² |
| 7) | A steel column in a multi-storied building carries an axial load of 250 kN. It is built up of two ISMC 350 channels connected by lacing. The lacing carries a load of |
| Option A: | 5 kN |
| Option B: | 6.25 kN |
| Option C: | 12.50 kN |
| Option D: | 18.75 kN |
| 8) | The design shear strength of beam of section ISWB 300 @ 48.1 kg/m is... |
| Option A: | 390.8 kN |
| Option B: | 490.2 kN |
| Option C: | 270.5 kN |
| Option D: | 291.3 kN |
| 9) | What is the maximum distance between two consecutive bolts (in tension) if the plate thickness is 10 mm? |
| Option A: | 160 mm |
| Option B: | 200 mm |
| Option C: | 250 mm |
| Option D: | 180 mm |
| 10) | A 20 mm diameter bolt of grade 4.6 is in double shear, the shearing strength of the bolt will be..... (assume threads in the shear planes) |
| Option A: | 45.25 kN |
| Option B: | 70.5 kN |
| Option C: | 90.5 kN |
| Option D: | 135.8 kN |

| | | |
|------------|--|----------------------|
| Q.2 | Solve any Two Questions out of Three | 10 marks each |
| A | Two ISA 75×50×8 are connected to a gusset plate of thickness 10 mm on the same side by four M18 bolts of grade 4.6. Find the design tensile strength of the angle if (i) the gusset is connected to the longer leg (ii) the gusset is connected to the shorter leg. | |
| B | Design a laced column 10.5 m long to carry the factored axial load of 1000 kN. The column is restrained in position but not in direction at both ends. Provide a single lacing system. Use 2 channel sections placed as back-to-back. Assume steel of grade Fe 410 and bolts of grade 4.6. | |
| C | Design a welded plate girder of span 18 m and laterally supported throughout. It supports a UDL of 85 kN/m (excluding of self-weight) throughout the span. Design central | |

| | |
|--|---|
| | section of plate girder for bending and shear. Use Fe 410 |
|--|---|

| Q 3 | Solve any Two Questions out of Three | 10 marks each |
|------------|---|----------------------|
| A | Design a slab base for a column ISHB 300 @ 618 N/m subjected to a factored axial compressive load of 1200 KN when the load is transferred to the base plate by the direct bearing of column flanges. The base rests on a concrete pedestal of grade M20 | |
| B | Design a laterally supported beam of effective span 6 m subjected to a maximum bending moment of 150 KN.m and maximum shear force of 210 KN for the following data. Use steel of grade: Fe 410 (Check for deflection is not required) | |
| C | Design a strut of length 2.235 m in a roof truss. It is subjected to a factored compressive force of 50 KN (due to D.L and L.L) and factored tensile force of 17.80 KN (due to D.L and W.L). Use Fe 410, 4.6 as bolt grade. Use 20 mm Bolt diameter. | |

| Q 4 | Solve any Two Questions out of Three | 10 marks each |
|------------|--|----------------------|
| A | Design a column using ISHB Section. The column is of length 3.5 m and supports factored load of 550 KN, the column is effectively restrained in position and direction at both the ends. Use Fe 410. | |
| B | A tie member consists of a double angle section, each 80 mm x 80 mm X 8 mm welded on the opposite side of a 12 mm thick gusset plate. Design a fillet weld for making the connections. The factored tensile force in the member is 300 KN. Draw a sketch showing the details. | |
| C | Design a bolted bracket connection to transfer an end reaction of 300 KN with an eccentricity of 170 mm. The steel used is of grade Fe 410. Use 20 mm diameter bolt of grade 4.6. The thickness of the bracket plate is 10 mm and the column section is ISHB 200 @ 365.91 N/m. | |

| | |
|--|---|
| | section of plate girder for bending and shear. Use Fe 410 |
|--|---|

| Q 3 | Solve any Two Questions out of Three | 10 marks each |
|------------|---|----------------------|
| A | Design a slab base for a column ISHB 300 @ 618 N/m subjected to a factored axial compressive load of 1200 KN when the load is transferred to the base plate by the direct bearing of column flanges. The base rests on a concrete pedestal of grade M20 | |
| B | Design a laterally supported beam of effective span 6 m subjected to a maximum bending moment of 150 KN.m and maximum shear force of 210 KN for the following data. Use steel of grade: Fe 410 (Check for deflection is not required) | |
| C | Design a strut of length 2.235 m in a roof truss. It is subjected to a factored compressive force of 50 KN (due to D.L and L.L) and factored tensile force of 17.80 KN (due to D.L and W.L). Use Fe 410, 4.6 as bolt grade. Use 20 mm Bolt diameter. | |

| Q 4 | Solve any Two Questions out of Three | 10 marks each |
|------------|--|----------------------|
| A | Design a column using ISHB Section. The column is of length 3.5 m and supports factored load of 550 KN, the column is effectively restrained in position and direction at both the ends. Use Fe 410. | |
| B | A tie member consists of a double angle section, each 80 mm x 80 mm X 8 mm welded on the opposite side of a 12 mm thick gusset plate. Design a fillet weld for making the connections. The factored tensile force in the member is 300 KN. Draw a sketch showing the details. | |
| C | Design a bolted bracket connection to transfer an end reaction of 300 KN with an eccentricity of 170 mm. The steel used is of grade Fe 410. Use 20 mm diameter bolt of grade 4.6. The thickness of the bracket plate is 10 mm and the column section is ISHB 200 @ 365.91 N/m. | |

Sub: WRE, Sem VI
Date: 21/05/2022
Civil, R.19

University of Mumbai
Examinations Summer 2022

Time: 2hour 30 minutes Max. Marks: 80

| Q1. | Choose the correct option for following questions. All the Questions are compulsory and carry equal marks |
|-----------|---|
| 1. | For growing irrigated paddy, the ideal water application method is: |
| Option A: | drip irrigation |
| Option B: | flood irrigation |
| Option C: | zigzag irrigation |
| Option D: | sprinkler irrigation |
| 2. | Dupuit's assumptions are valid for |
| Option A: | artesian aquifer |
| Option B: | confined aquifer |
| Option C: | leaky aquifer |
| Option D: | unconfined aquifer |
| 3. | If the intensity of irrigation for Kharif is 45% and that for Rabi is 60%; then the annual intensity of irrigation, is: |
| Option A: | 45% |
| Option B: | 60% |
| Option C: | 100% |
| Option D: | 105% |
| 4. | A hietograph is a graphical representation of |
| Option A: | Rainfall intensity and time |
| Option B: | Rainfall depth and time |
| Option C: | Discharge and time |
| Option D: | Cumulative rainfall and time |
| 5. | In case of a flowing well, the piezometric surface |
| Option A: | is always below the ground level |
| Option B: | is always above the ground level |
| Option C: | is always at the ground level |
| Option D: | may be above or below the ground level |
| 6. | One amongst the following is Canal ESCAPE |
| Option A: | Cutting Escape |
| Option B: | Scouring Escape |
| Option C: | Unbalanced Escape |
| Option D: | Balanced Escape |
| 7. | For no tension to be develop in the gravity dam the eccentricity of the resultant force should be: |
| Option A: | $< b/2$ |
| Option B: | $< b/3$ |
| Option C: | $< b/4$ |
| Option D: | $< b/6$ |
| 8. | Which of the following is not a type of precipitation? |

| | |
|-----------|---|
| 9. | Which of the following is a false statement? |
| Option A: | Canal lining reduces seepage losses |
| Option B: | Canal lining is a permeable layer |
| Option C: | Canal lining improves the life of a canal |
| Option D: | Canal lining improves discharge capacity of a canal |
| 10. | According to Lacey's, what is the proposed shape of regime channel? |
| Option A: | Hyper-bolic |
| Option B: | Circular |
| Option C: | Rectangular |
| Option D: | Semi-elliptical |

Q.2 20 Marks

| | |
|---|--|
| Solve any four Questions out of Six 5 marks each | |
| 1. | Compare Kennedy and Lacey's theories |
| 2. | Define the following: aquifer, aquifuge, aquiclude, transmissibility, drawdown, cone of depression. |
| 3. | Derive the relation between duty, delta and base period. Also find delta for a crop if duty for a base period of 100 days is 1800 ha/cumecs. |
| 4. | Explain any one type of Automatic rain gauge instrument with sketch. |
| 5. | Explain in detail with a neat sketch different Zones of Storage of Reservoirs |
| 6. | Describe hydrograph and hietograph. Also draw neat diagrams |

Q.3 20 Marks

| | | | | | | | | | | | | | | | |
|--|--|----|----|----|-----|-----|-----|-----|-----|----|----|----|----|----|----|
| Solve any Two Questions out of Three 10 marks each | | | | | | | | | | | | | | | |
| 1. | Using Lacey's theory, design an irrigation channel for the following data: Discharge Q=50 cumecs, silt factor f=1, side slopes = 0.5H:1V | | | | | | | | | | | | | | |
| 2. | Describe in detail the failures of an earthen dam, along with neat diagrams | | | | | | | | | | | | | | |
| Given below are the ordinates of a 6h unit hydrograph for a catchment. Calculate the ordinates of direct runoff hydrograph due to a rainfall excess of 4.5 | | | | | | | | | | | | | | | |
| Time hrs | 0 | 3 | 6 | 9 | 12 | 15 | 18 | 24 | 30 | 36 | 42 | 48 | 54 | 60 | 69 |
| Flow cumecs | 0 | 25 | 50 | 85 | 125 | 160 | 185 | 160 | 110 | 60 | 36 | 25 | 16 | 8 | 0 |

Q.4 20 Marks

| | |
|---|--|
| Solve any Two Questions out of Three 10 marks each | |
| 1. | Define Precipitation. Explain any one type of precipitation and explain different forms of precipitation |
| 2. | Describe with the help of sketches various types of Cross Drainage Work. |
| 3. | For a homogenous Earthen Dam with height = 52m and freeboard of 2m, flow net was constructed and following results were obtained. Number of potential drops = 25, Number of Flow Channels = 4. Dam has horizontal filter 40 m in length at itsdownstream end. Calculate discharge per meter length of dam . A) Soil is Iso-tropic andthe co-efficient of permeability of the dam is 3×10^{-5} m/sec B) Soil is Anisotropic Soilwhere $k_x = 4 \times 10^{-4}$ m/sec and $k_y = 10^{-6}$ m/sec |

| | |
|------------|---|
| Q1. | Choose the correct option for following questions. All the Questions are compulsory and carry equal marks |
| 1. | A cohesionless soil having an angle of shearing resistant of ϕ , is standing at a slope angle of i . The factor of safety of the slope is |
| Option A: | $\tan i / \tan \phi$ |
| Option B: | $\tan i - \tan \phi$ |
| Option C: | $\tan \phi / \tan i$ |
| Option D: | $\tan \phi - \tan i$ |
| 2. | The passive earth pressure of a soil is proportional to |
| Option A: | $\tan (45 - \phi)$ |
| Option B: | $\tan (45 + \phi)$ |
| Option C: | $\tan^2 (45 - \phi)$ |
| Option D: | $\tan^2 (45 + \phi)$ |
| 3. | Coefficient of consolidation of a soil is affected by |
| Option A: | Compressibility and Permeability of soil |
| Option B: | Compressibility only |
| Option C: | Permeability only |
| Option D: | Compaction |
| 4. | The percentage reduction in the bearing capacity of a strip footing resting on sand when the water level is at the base of the footing and when the water level is at a depth much greater than the width of footing, is approximately. |
| Option A: | 5 |
| Option B: | 25 |
| Option C: | 50 |
| Option D: | 75 |
| 5. | The factor of safety F_c with respect to cohesive strength is based on the assumption that |
| Option A: | Frictional force is fully mobilized |
| Option B: | Frictional force is zero |
| Option C: | Total cohesive resistance is zero |
| Option D: | Both friction and cohesion are mobilized |
| 6. | A square pile 300 mm size penetrates soft clay with cohesion of 85 KPa and a depth of 18 m and rest on stiff soil. Determine the capacity of pile by skin friction. Assume an adhesion factor of 0.75 |
| Option A: | 1085 kN |
| Option B: | 1377 kN |
| Option C: | 1550 kN |
| Option D: | 1455 kN |

| | |
|-----------|--|
| | For a sand having an angle of internal friction of 22° , the ratio of active to lateral earth pressure will be. |
| Option A: | 0.482 |
| Option B: | 0.206 |
| Option C: | 0.166 |
| Option D: | 0.111 |
| 8. | The plate load test is conducted on clayey strata by using a plate of $0.45\text{m} \times 0.45\text{m}$ dimensions, and the ultimate load per unit area for the plate is found to be 200 kPa. The ultimate bearing capacity of a 2.2 m wide square footing would be |
| Option A: | 180 kPa |
| Option B: | 450 kPa |
| Option C: | 220 kPa |
| Option D: | 200 kPa |
| 9. | By which process some compression of soil takes place, after the hydrostatic pressure reduces to zero? |
| Option A: | Secondary consolidation |
| Option B: | Primary consolidation |
| Option C: | Load increment |
| Option D: | Effective pressure |
| 10. | Basement walls are generally designed for |
| Option A: | Active pressure |
| Option B: | Passive pressure |
| Option C: | At rest pressure |
| Option D: | Lateral pressure |

| | |
|------------|--|
| Q2. | |
| A | Solve any Two 5 marks each |
| i. | Explain pre consolidation pressure with appropriate figure. |
| ii. | Derive an expression for the factor of safety when the slope of an earthen dam is dry. Assume the soil to possess both cohesion and friction. |
| iii. | What are the three standard triaxial shear tests with respect to drainage conditions? Explain with reasons the situations for which each test is to be preferred. |
| B | Solve any One 10 marks each |
| i. | A layer of soft clay is 7 m thick and lies under a newly constructed building. The weight of sand overlying the clayey layer produces a pressure of 240kN/m^2 and the new construction increases the pressure by 100kN/m^2 . If the compression index is 0.45, compute the settlement. Water content is 41% and specific gravity of grains is 2.65 |
| ii. | A cylindrical sample of saturated clay 4cm in diameter and 8cm high was tested in an unconfined compression apparatus. Find the unconfined compression strength, if the specimen failed at an axial load of 360N, when the axial deformation was 8mm. Find the shear strength parameters if the angle made by the failure plane with the horizontal plane was recorded as 50° . Verify results graphically. |

| | |
|------------|--|
| Q3. | |
| A | Solve any Two 5 marks each |
| i. | Determine the active and passive earth pressure given the following data: Height of the retaining wall = 10m, angle of internal friction of the backfill soil is 25° and dry unit weight of backfill is 17kN/m^3 . Ground water table is at the top of the retaining wall. |
| ii. | Compare Rankine's and Coulombs lateral earth pressure theory. |

| | |
|------|--|
| iii. | State assumptions in Terzaghi's bearing capacity analysis. Explain effect of water table on the bearing capacity of soil. |
| B | Solve any One 10 marks each |
| i. | A concrete pile 350 mm diameter is driven into dense sand for a depth of 8.5. Estimate: (i) The safe load acting on the pile. (ii) Safe load if the water table exists at 2 m below the ground surface. Consider following properties of the sand: angle of internal friction = 35° , unit weight = 20 kN/m^3 , coefficient of friction between sand and pile = 0.7, coefficient of earth pressure = 1. |
| ii. | Compute the safe bearing capacity of a continuous footing 1.8m wide and located at a depth of 1.2m below ground level in a soil with unit weight 20 kN/m^3 , $c = 20 \text{ kN/m}^2$ and angle of internal friction 20° . Assume a factor of safety of 2. Terzaghi's bearing capacity factors for angle of internal friction ($=20^\circ$) are $N_c = 17.7$, $N_q = 7.4$ and $N_\gamma = 5.0$. What is the permissible load per meter run of the footing? |

| | |
|------------|--|
| Q4. | |
| A | Solve any Two 5 marks each |
| i. | Explain Swedish Circle Method for cohesive soil for stability analysis of slopes. |
| ii. | Define Initial consolidation, Primary consolidation and Secondary consolidation. |
| iii. | What are the causes and effects of Negative skin friction? Explain the remedial measures to minimize it. |
| B | Solve any One 10 marks each |
| i. | Explain classification of Pile Foundation. Show how the static bearing capacity of the Pile foundations can be estimated. |
| ii. | A cantilever retaining wall of 7meter height retains sand. The properties of the sand are void ratio = 0.5, angle of internal friction = 30° and specific gravity = 2.7. Using Rankine's theory determine the active earth pressure at the base when the backfill is (1) dry, (2) saturated (3) submerged and also the resultant active force in each case. |

Q.P code: 93528

27/05/2022

University of Mumbai
Examination May 2022

Examinations Commencing from 17 May 2022

Program: **Civil Engineering**

Curriculum Scheme: Rev - 2019

Examination: TE Semester: VI

Course Code: CEC604

Course Name: Environmental Engineering

Time: 2hour 30 minutes

Max. Marks: 80

170522_R19_TE_VI_CEC604_QP1

| Q1. | Choose the correct option for following questions. All the Questions are compulsory and carry equal marks |
|-----------|---|
| 1. | water can be easily diverted for fire fighting in this system |
| Option A: | Grid iron system |
| Option B: | Dead end system |
| Option C: | Radial system |
| Option D: | Gravity system |
| 2. | Within first five days BOD demand get satisfied by |
| Option A: | 48% |
| Option B: | 58% |
| Option C: | 78% |
| Option D: | 68% |
| 3. | Which water treatment process is done after filtration of water? |
| Option A: | Primary sedimentation |
| Option B: | Secondary sedimentation |
| Option C: | Disinfection |
| Option D: | Flocculation |
| 4. | Which of the following is the basic indicator of river health |
| Option A: | BOD |
| Option B: | COD |
| Option C: | DO |
| Option D: | ThOD |
| 5. | In which type of aerator, the flow of water is divided into fine streams and small droplets. |
| Option A: | Spray aerator |
| Option B: | Cascade aerator |
| Option C: | Inclined apron aerator |
| Option D: | Gravel bed aerator |

| | |
|-----------|---|
| 6. | A right angle sleeve made of brass and gun metal is called |
| Option A: | Goose neck |
| Option B: | Ferrule |
| Option C: | Service pipe |
| Option D: | Stop cock |
| 7. | What indicates the permanent hardness when alum is added to water |
| Option A: | Al(OH) ₃ |
| Option B: | Ca SO ₄ |
| Option C: | CO ₂ |
| Option D: | Ca(OH) ₂ |
| 8. | Aeration is not required in this sewage processing unit |
| Option A: | Trickling filter |
| Option B: | Oxidation pond |
| Option C: | Activated sludge process |
| Option D: | Septic tank |
| 9. | Which of the following is called secondary air pollutant |
| Option A: | PANs |
| Option B: | Carbon dioxide |
| Option C: | Carbon monoxide |
| Option D: | Nitrogen dioxide |
| 10. | This is a suitable method of disposal of solid waste containing organic waste |
| Option A: | Incineration |
| Option B: | Landfilling |
| Option C: | Composting |
| Option D: | Chemical precipitation |

Attempt any three questions out of following

| Q2 (A) | Solve any two out of three | 5 marks each |
|--------|--|---------------|
| 1 | Explain the factors affecting the location of intake structure | |
| 2 | Explain the mechanism of coagulation and flocculation | |
| 3 | Determine the velocity and rate flow of sewage flowing through the sewer of diameter 300mm and running half full. Sewer is laid at the gradient of 1 in 300. Take Manning's constant $N=0.013$ | |
| Q2 (B) | Solve any one of the following | 10 marks each |
| 1 | Design the rapid sand filter with under drainage system to treat 7.5MLD Of raw water. Assume rate of filtration 6000 lit/hr/m ² , assume 5% water and 30 minutes required for back washing. | |
| 2 | Following is the data for the single stage trickling filter a) Sewage flow= 4.5MLD b) BOD ₅ of raw sewage= 250mg/l | |

| | | |
|---------------|---|----------------------|
| | c) recirculation ratio = 2 d) depth of media = 2M e) BOD of effluent = 25mg/l f) BOD removal in primary tank = 30% Determine size of single stage trickling filter and find out efficiency. | |
| Q3 (A) | Solve any Four Questions out of six | 5 marks each |
| 1 | Write down the effect of air pollution on human health | |
| 2 | Show that $70\text{dB} + 70\text{dB} \neq 140\text{dB}$ | |
| 3 | Explain in detail self-purification capacity of stream | |
| 4 | Explain functional elements of solid waste management | |
| 5 | Explain the process of break point chlorination | |
| 6 | .Explain different methods of water softening. | |
| Q4 (A) | Solve any Two Questions out of Three | 5 marks each |
| 1 | Differentiate between one pipe and two pipe system | |
| 2 | Chlorine usage in treatment of 20 MLD of water is 16Kg/day. The residual After 10 minute of contact is 0.2 mg/l. Calculate chlorine dosage in mg/l and chlorine demand of water. | |
| 3 | A sewage sample has 5 day BOD of 180 mg/l at 20°C . calculate the 2 day BOD of the sample at 37°C . Take $K_D = 0.1$ | |
| B | Solve any one of the following | 10 marks each |
| 1 | Design a Septic tank for housing colony of 200 people, water supply rate is 150l/c/day and tank is to be clean once in two years. Draw the sectional sketch showing all the details. | |
| 2 | Design the sedimentation tank to treat 10 MLD of raw water. Assume flow velocity 0.25m/minute, overflow rate 600 lit/hr./m ² and detention time of 4hour. | |

Q.P. Code: 94060

University of Mumbai

Examinations Summer 2022

Program: T.E (Civil) Rev 2019 (Choice Based)

Curriculum Scheme: Rev 2019

Examination: TE Semester: VI

Course Code: CE-DLO 6013

Course Name: Construction Equipment & Techniques

Time: 2 hour 30 minutes

Max. Marks: 80

| Q1. | Choose the correct option for following questions. All the Questions are compulsory and carry equal marks (20 marks) |
|-----------|--|
| 1 | The raw material used in an atomic power plant is |
| Option A: | Sodium |
| Option B: | Uranium. |
| Option C: | Calcium |
| Option D: | Magnesium |
| 2 | The formwork suitable for constructing similar units in a mass housing project is |
| Option A: | Jump formwork |
| Option B: | Collapsible formwork |
| Option C: | Modular shuttering |
| Option D: | Slip formwork |
| 3 | The rate of raising slip form is |
| Option A: | 50 cm/hr. |
| Option B: | 100 cm/hr. |
| Option C: | 30 to 45 cm/hr. |
| Option D: | 10 to 15 cm/hr. |
| 4 | Well point system is a |
| Option A: | Well construction technique |
| Option B: | Dewatering technique |
| Option C: | Drilling technique |
| Option D: | Soil improvement technique |
| 5 | Removal of debris from inner portion of a tunnel to open atmosphere is called |
| Option A: | Lead |
| Option B: | Lift |
| Option C: | Scrapping |
| Option D: | Mucking |
| 6 | Damages to underground utility lines can easily be located using |
| Option A: | Great trigonometrical radars |
| Option B: | Underground utility locator |
| Option C: | Ground positioning remotes |
| Option D: | Ground penetrating radar |

| | |
|-----------|---|
| 7 | The train which floats over its guide system is |
| Option A: | Maglev |
| Option B: | Mono |
| Option C: | Metro |
| Option D: | Tube train |
| 8 | The method of Tunneling in which least interruption of traffic is possible is |
| Option A: | Cut and Cover Method |
| Option B: | Needle Beam Method |
| Option C: | TBM Method |
| Option D: | English Method |
| 9 | Thermal power plants use water as a |
| Option A: | cleaning agent |
| Option B: | source of power |
| Option C: | backwashing agent |
| Option D: | working fluid |
| 10 | The equipment used to remove off old bituminous pavement for laying new layer is called |
| Option A: | Sack rammer |
| Option B: | Jack hammer |
| Option C: | Tack hammer |
| Option D: | Back rammer |

| | | |
|-------------------------|--|--------------------|
| Q2 (20 Marks) | Solve any Four out of Six | 5 mark each |
| i | Explain balancing of equipment with a suitable exam. | |
| ii | Define a) Equipment Suitability b) Ownership Cost c) Reactive Maintenance and Proactive Maintenance d) Cycle Time e) operating cost of equipment | |
| iii | Differentiate between conventional and modern methods of formwork | |
| iv | What is NATM? Write advantages and limitations of NATM. | |
| v | Write a note on cut and cover method of tunnel construction | |
| vi | State the advantages of prefabricated housing system | |

| | | |
|-------------------------|--|---------------------|
| Q3 (20 Marks) | Solve any Two Questions out of Three | 10 mark each |
| i | Enlist the different methods of tunneling in soft soil. State the various stages in construction of tunnels along with the equipment required. Describe with neat sketches any one method. | |
| ii | Describe Incremental launching method of bridge construction | |
| iii | Describe in detail with diagram about slip and jump formwork | |

| | |
|---------------------------------|---|
| Q4. (20 Marks) | |
| A | Solve any Two 5 marks each |
| i. | What is ground penetrating radar (GPR)? What is use of the GPR system? |
| ii. | What are maglev trains? Explain the working of maglev trains. |
| iii | Give the layout of a Hydropower station & explain the techniques for setting up the same. |
| B | Solve any ONE 10 mark each |
| i. | What are different techniques for demolition of buildings. |
| ii. | Explain different types of earth moving equipment and brief the suitability of each. |

ISLAM'S KALSEKAR
ENGINEERING & TECHNOLOGY

AIKTC

MUMBAI - INDIA

PHARMACY,
NEW PANVEL

University of Mumbai

Examination Second Half 2021 under cluster __ (Lead College: _____)

Q.P. Code: 93250

Program: Civil Engineering
Curriculum Scheme: Rev2019

31/05/2022

Examination: TE Civil Semester VI

Course Code: CEDLO6017 and Course Name: **Traffic Engineering and Management**

Time: 2 hour 30 minutes

Max. Marks: 80

| Q1. | Choose the correct option for following questions. All the Questions are compulsory and carry equal marks |
|-----------|---|
| 1. | Most severe vehicular conflict on intersection is |
| Option A: | Diverging conflict |
| Option B: | Merging conflict |
| Option C: | Crossing conflict |
| Option D: | Distracted conflict |
| 2. | If the average of front bumper to front bumper distance between 2 successive vehicles on a single lane is 10 meters than the average density of that lane will be |
| Option A: | 10000 veh/km |
| Option B: | 1000 veh/km |
| Option C: | 100 veh/km |
| Option D: | 10 veh/km |
| 3. | Which of the traffic signal method is based on saturation flow? |
| Option A: | Trial cycle method |
| Option B: | Webster method |
| Option C: | IRC method |
| Option D: | Approximate method |
| 4. | QKV curve plotting is based on assumption that |
| Option A: | V-K plot is linear |
| Option B: | Q-K plot is linear |
| Option C: | Q-V plot is linear |
| Option D: | V-K plot is parabolic |
| 5. | For a 2-phase signal, If the amber time is 4 sec and the green signal time is 25sec for N-S direction, find the red signal time for E-W direction. |
| Option A: | 22sec |
| Option B: | 21sec |
| Option C: | 28sec |
| Option D: | 29sec |
| 6. | Distance between two consecutive vehicles in same lane is called as |
| Option A: | Time Headway |
| Option B: | Space Headway |
| Option C: | Optimum Density |
| Option D: | Jam Density |

| C | Find the flow in both directions | | | | | | |
|---|----------------------------------|-----------|--------------|--------|------------|-----------|-------------------------------|
| | Trip | Direction | Journey time | Delay | overtaking | overtaken | Vehicle in opposite direction |
| | 1 | N-S | 6'32'' | 1'40'' | 7 | 4 | 258 |
| | 2 | S-N | 7'14'' | 1'50'' | 5 | 3 | 176 |
| | 3 | N-S | 6'50'' | 1'30'' | 5 | 3 | 270 |
| | 4 | S-N | 7'40'' | 2'0'' | 3 | 1 | 200 |
| | 5 | N-S | 6'10'' | 1'10'' | 1 | 5 | 250 |
| | 6 | S-N | 8'0'' | 2'22'' | 5 | 2 | 170 |
| | 7 | N-S | 6'28'' | 1'40'' | 2 | 5 | 290 |
| 8 | S-N | 7'30'' | 1'40'' | 3 | 2 | 160 | |

| | | | | | |
|------------------|---|---------------|------|------|------|
| Q3 (20 Marks) | Solve any Two out of Three | 10 marks each | | | |
| A | Design 2 phase signal using Webster's method where only straight traffic is permitted | | | | |
| | | N | S | E | W |
| | DESIGN FLOW | 600 | 800 | 560 | 1200 |
| | SATURATED FLOW | 2000 | 2400 | 1900 | 3000 |
| B | Find the accumulation, total parking load, average occupancy and efficiency of the parking lot. | | | | |
| | Time | IN | Out | | |
| | 5 | 2 | 3 | | |
| | 10 | 4 | 2 | | |
| | 15 | 2 | 4 | | |
| | 20 | 4 | 5 | | |
| | 25 | 3 | 7 | | |
| | 30 | 8 | 2 | | |
| | 35 | 2 | 7 | | |
| | 40 | 4 | 2 | | |
| | 45 | 4 | 6 | | |
| | 50 | 1 | 4 | | |
| 55 | 3 | 3 | | | |
| 60 | 5 | 2 | | | |
| C | 61-year-old Sai was involved in an accident on the NH highway during an off-peak hour, just 5 hours later at the same location 31-year-old Tom was involved in an accident. Look for any correlation between accidents & driver age explain in detail | | | | |